

No. KK-2006-2193

Date: Nov. 07, 2006

Attention:

Your ref. No.:

Your Part No.: RK27112MC01E

SPECIFICATIONS

ALPS;

MODEL: RK27112MC01E
(50kAX2)

Spec. No.:

Sample No.: F 3 5 1 0 0 7 3 M

RECEIPT STATUS

RECEIVED

By Date

Signature

Name

Title

ALPS[®]
ALPS ELECTRIC CO., LTD.

Head Office
1-7, Yukigaya-otsuka-cho, Ota-ku, Tokyo, 145-8501 Japan
Phone,+81(3)3726-1211

DSG'D

Y. Ohya

APP'D

S. Ikenoue

ENG. DEPT. DIVISION

Sales

B6523

Q1003#03A (EA)

SPECIFICATIONS

1. THIS SPECIFICATIONS APPLY TO RK27112MC01E POTENTIOMETER.

2. CONTENTS OF THIS SPECIFICATIONS.

5K272AMS-4

K272AMCOOY

4K16M-1

4K-1

3. MARKING

• MARKING ON ALL UNITS

DATE CODE, RESIST. VALUE, TAPER

4. REMARKS

- FURNISH PACKAGE

NUT:1 WASHER:1

• NOTES

• Silver printed patterns are coated with carbon as a protection against sulphuration.

• Marking ⇒ in specifications shows standard and condition for application.

• CAUTION

Regardless of the suggested applications of these products being introduced in the specifications, when using them for equipment and devices requiring a high degree of safety, respective manufacturers will please preserve safety of the planned equipment and devices by providing necessary protective circuits and redundancy circuits and reconfirm if safety is being duly preserved.


Products being introduced in the specifications have been designed and manufactured for applications to ordinary electronic equipment and devices such as the AV equipment, electric home appliances, office machines and communications equipment. Consequently, when employing these products for applications requiring a high degree of safety and reliability such as the medical equipment, aviation and aircraft equipment, space equipment and burglar alarm equipment, the using manufacturers will please thoroughly study the proprieties of these products for the planned applications.

Although we are exerting our best efforts to maintain the quality of these products, we cannot guarantee that they will never cause short circuiting and open circuitry. Therefore, when designing an equipment or device with which the priority is given to the safety, you will please carefully study the influences to the whole equipment of a single function failure of Potentiometers and Encoders in advance to make out a fail-safe design providing.

CLASSNO.	TITLE	SPECIFICATIONS
		<p>Feature This is a potentiometer with D.C. magnet motor and it is adjustable by both manual shaft and motor.</p> <p>Temperature for operating and storage 1. Dimensions : See attached drawing 2. Operating temperature : -10 °C ~ +70 °C 3. Storage temperature : -20 °C ~ +80 °C 4. Motor : D.C. magnet motor (With 6V Disk Varistor)</p> <p>Mechanical specifications 1. Operation : manual operation and motor drive 2. Total rotational angle : $300^{\circ} \pm 5^{\circ}$ 3. Rotational speed : 12 ± 3 sec/300° (at 4.5V D.C. applied to motor) 4. Direction of rotation : C.W. rotation at normal polarity. (When the potentiometer is looked at from the shaft side.) 5. Mechanical noise : Continuous, monotonous, not unpleasant sound to be heard. To be mutually discussed when questionable. 6. Rotational torque : $15 \sim 45$ mN·m (at 1000 rpm) (Rotational speed 60°/sec.) 7. Stopper strength of shaft with manual operation : No damage with an application of 0.9 N·m (at 1000 rpm) with motor drive : Shaft must be slipped at the both ends of manual rotation. 8. Bushing nut tightening strength: Δ Tightening torque to be no greater than 1.5 N·m (at 1000 rpm). (Pay attention otherwise the strength may not be assured.) 9. Push / pull strength : No damages with an application of push or pull force 1.0 N (at 1000 rpm) for 10 sec. 10. Resistance to soldering heat : After soldering there shall be no evidence of poor contact between resistance element and terminals, or any physical damage as a result of the test. The terminal of the potentiometer less than 350 °C and within 5 sec. The terminal of the motor less than 350 °C and within 2 sec.</p>

CLASSNO.	TITLE	SPECIFICATIONS																				
		<p>Electrical specifications 50kΩ</p> <p>1. Total resistance : Nominal total resistance $\pm 20\%$ (10kΩ \leq R \leq 2MΩ) 2. Rated voltage : 30V A.C. This potentiometer is designed for A.C. voltage only. 3. Resistance taper : See (HSA02) 4. Maximum attenuation level at full C.C.W. position :</p> <table border="1"> <thead> <tr> <th>Total resistance</th> <th>Attenuation level</th> </tr> </thead> <tbody> <tr> <td>R \geq 100kΩ</td> <td>100 dB min.</td> </tr> <tr> <td>100kΩ > R \geq 50kΩ</td> <td>90 dB min.</td> </tr> <tr> <td>50kΩ > R \geq 10kΩ</td> <td>80 dB min.</td> </tr> </tbody> </table> <p>5. Insertion loss at full C.W. position : 0.1 dB max. <small>measure between (R1, R2) term 1-2 output V</small> 6. Gang error : <small>(term 1-3 in dB V)</small></p> <table border="1"> <thead> <tr> <th>Total resistance</th> <th>Gang error</th> </tr> </thead> <tbody> <tr> <td>R \geq 50kΩ</td> <td>3 dB max. between -70 dB less than -60 dB</td> </tr> <tr> <td>50kΩ > R \geq 20kΩ</td> <td>2 dB max. between -60 dB ~ 0 dB</td> </tr> <tr> <td>20kΩ > R \geq 10kΩ</td> <td>3 dB max. between -60 dB less than -40 dB</td> </tr> <tr> <td></td> <td>2 dB max. between -40 dB ~ 0 dB</td> </tr> <tr> <td></td> <td>3 dB max. between -60 dB ~ 0 dB</td> </tr> </tbody> </table> <p>7. Sliding noise : Less than 47mV measured by JIS C 6443. (Neglected a impulsive noise at the C.W. and C.C.W. ends of position.) 8. Insulation resistance Potentiometer section : More than 100MΩ at 500V D.C. Motor section : More than 1MΩ at 100V D.C. 9. Withstand voltage Potentiometer section : 500V A.C. for 1 minute. 10. Supply voltage of motor : 4~6V D.C. 11. Motor current (at 4.5V D.C. applied to motor) Normal operation : 100mA max. Slipping operation : 150mA max. at both ends : 4.5V D.C.</p> <p>Endurance specifications 1. Rotational life : 15,000 cycles min.</p>	Total resistance	Attenuation level	R \geq 100k Ω	100 dB min.	100k Ω > R \geq 50k Ω	90 dB min.	50k Ω > R \geq 10k Ω	80 dB min.	Total resistance	Gang error	R \geq 50k Ω	3 dB max. between -70 dB less than -60 dB	50k Ω > R \geq 20k Ω	2 dB max. between -60 dB ~ 0 dB	20k Ω > R \geq 10k Ω	3 dB max. between -60 dB less than -40 dB		2 dB max. between -40 dB ~ 0 dB		3 dB max. between -60 dB ~ 0 dB
Total resistance	Attenuation level																					
R \geq 100k Ω	100 dB min.																					
100k Ω > R \geq 50k Ω	90 dB min.																					
50k Ω > R \geq 10k Ω	80 dB min.																					
Total resistance	Gang error																					
R \geq 50k Ω	3 dB max. between -70 dB less than -60 dB																					
50k Ω > R \geq 20k Ω	2 dB max. between -60 dB ~ 0 dB																					
20k Ω > R \geq 10k Ω	3 dB max. between -60 dB less than -40 dB																					
	2 dB max. between -40 dB ~ 0 dB																					
	3 dB max. between -60 dB ~ 0 dB																					
		<table border="1"> <tr> <td>DATE</td> <td>APPR.</td> <td>CHKD.</td> <td>ISSCD.</td> <td>TITLE</td> </tr> <tr> <td>1981.11.18</td> <td>M.S.</td> <td>Y.B.</td> <td>Aug. 10, 81</td> <td>Aug. 6, 81</td> </tr> <tr> <td>SYMB.</td> <td>DATE</td> <td>APPR.</td> <td>CHKD.</td> <td>ISSCD.</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> </table> <p>ALPS ELECTRIC CO., LTD.</p> <p>DOCUMENT NO. 5K272AMS-4</p>	DATE	APPR.	CHKD.	ISSCD.	TITLE	1981.11.18	M.S.	Y.B.	Aug. 10, 81	Aug. 6, 81	SYMB.	DATE	APPR.	CHKD.	ISSCD.					
DATE	APPR.	CHKD.	ISSCD.	TITLE																		
1981.11.18	M.S.	Y.B.	Aug. 10, 81	Aug. 6, 81																		
SYMB.	DATE	APPR.	CHKD.	ISSCD.																		

ALPS ELECTRIC CO., LTD
1-7 YUKIGAYA OTSUKA-CHO OTA-KU TOKYO JAPAN



AT 180° C.W. SHAFT ROTATION FROM FULL C.C.W. POSITION, VOLTAGE PERCENT SHALL FALL WITHIN THE LIMITS OF 15 - 30PERCENT.

SYMB	DATE	APPD	CHKD	DSGD	SCALE	TITLE	DOCUMENT NO.
15-05-31	7.17.76	S.S.	S.S.	APPD	mm	RESISTANCE TAPER	H S A O 2
CHKD							
DSGD							


FOR

< はんだ付け時のご注意事項 >

図のようにP. W. Bの上面に はんだ付けをする配線は、お避け下さい。

Caution for soldering

Please avoid soldering on upper surface of P. W. B. as shown



SYMB	DATE	APPD	CHKD	DSGD	SCALE	TITLE	DOCUMENT NO.
						RESISTANCE TAPER	4K-1
CHKD							
DSGD							


ALPS ELECTRIC CO., LTD.

FOR

CLASSNO.	TITLE	SPECIFICATIONS
	Note	<p>1.The standard test shall be subject to a temperature from 5 °C to 35 °C and relative humidity from 45% to 85%. Test shall be done under environmental requirements of a temperature of 20 ± 2 °C and relative humidity of 65 ± 5% if a decision is in question.</p> <p>2.Notice on motor</p> <p>1)Motor terminals shall not be bent more than twice.</p> <p>2)Soldering to the motor terminals shall be within a few second, not to cause the transformation of terminal base plastics. And, avoid that the flux flows into the motor. Pay special attention to the terminals when they are wave soldered.</p> <p>If the flux flows into the motor, it may cause a poor contact.</p> <p>3)Motor terminal should not be pressed inside the motor. It may cause a poor contact in the motor.</p> <p>4)Pay attention that a piece of iron and an alien substance are not crept into the motor.</p> <p>5)In operation, temperature around the motor produce an effect on the performance and life. Pay special attention in high temperature and humidity. Storage in high temperature and humidity, and in corrosive gas, shall be avoided.</p> <p>6)In case, using the adhesive agent and the seal agent etc.for fit up, make sure that there is no generation of the harmful gas for motor.(including all chemicals around the motor.) Pay special attention to cyanogen system adhesive agent and organically system silicone.</p>

CLASSNO.	TITLE	SPECIFICATIONS
	3.Power supply	<p>Regulated D.C. power supply shall be used. (ripple to be 1% max.)Motor terminal shall not be connected with fixed resistors in series. And supply current is to be 350mA min.</p> <p>4.Knob</p> <p>The material of the knob shall be insulation material. As potentiometer is not grounded, conductive material of the knob may cause a earth noise.</p> <p>5.The items except above mentioned items shall meet or exceed JIS C 6443.</p>


APPROVED	CHKD.	TITLE
APR 18 1990	APR 18 1990	ALPS ELECTRIC CO., LTD.
APR 18 1990	APR 18 1990	DSGD. NO.
APR 18 1990	APR 18 1990	DOCUMENT NO.
APR 18 1990	APR 18 1990	4K16M-1
SYMB.	DATE	APPD
		CHKD.
		DSGD.



上図は軸を反時計方向に
回し切った状態を示す。


SHAFT SHOWN IN FULL CCW POSITION

許容差の指定なき寸法の公差	
TOLERANCES UNLESS OTHERWISE SPEC	
BASIC DIMENSIONS	TOLERANCE
L ≤ 10	±0.3
10 < L < 100	±0.5
100 ≤ L	±0.8
角度 ANGULAR DIMENSION	±5°




取付寸法図 許容差±0.1
P.W.B. MOUNTING DETAIL
TOLERANCE ±0.1

VIEWED FROM MOUNTING SIDE
挿入側より



背面図



PART NO.		NAME		MATERIAL NAME & CODE		FINISH	
ALPS ELECTRIC CO., LTD.							
D.C. 4.5 V		UNIT mm		SCALE		TITLE 27形1軸2速 モータ駆動ボリューム組立図 図 3.27	
SYMB.		DATE	APPD.	CHKD.	DSGD.	DOCUMENT NO.	
		91.7.23	佐藤	投5 91.7.23 山下	設5 91.7.23 山口	K272AMCOOY	

87.3g

OR